

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) VHG-SKERO-50-100

Product Name Sulfur Standard: S @ 50 μg/q (0.0050 wt%) in Kerosene

Unique Formula Identifier (UFI) T3D5-30XN-600V-3UYK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Laboratory use

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

## **Supplier**

LGC Limited Queens Road Teddington Middlesex TW11 0LY UNITED KINGDOM :+44 (0) 20 8943 7000 Fax :+44 (0) 20 8943 2767 eMail : gb@lgcstandards.com

Web: www.lgcstandards.com

For further information, please contact

E-mail address sds-request@lgcgroup.com

1.4. Emergency telephone number

Emergency Telephone For Hazardous Materials or Dangerous Goods Incident

Spill, Leak, Fire Exposure, or Accident

Call CHEMTREC:

USA & Canada 1-800-424-9300 Rest of the world +1 703-741-5970

Emergency Telephone - §45 - (EC)1	272/2008
Europe	112

EGHS / EN Page 1/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

## VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

Austria	No information available
Bulgaria	
Croatia	
Cyprus	
Czech Republic	
Denmark	
France	
Hungary	
Ireland	
Italy	
Lithuania	
Luxembourg	(+352) 8002 5500 Free telephone number with a 24/7 access in French, Dutch and English.
Netherlands	
Norway	
Portugal	
Romania	
Slovakia	
Slovenia	
Spain	
Sweden	
Switzerland	

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

#### 2.2. Label elements

265-149-8

Contains Kerosine: distillates, hydrotreated light (D94/69 p1249) 4





Signal word Danger

EGHS / EN Page 2/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

#### **Hazard statements**

H304 - May be fatal if swallowed and enters airways

H226 - Flammable liquid and vapour

#### Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other hazards

No information available.

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** 

<u> </u>		
Chemical name	EU - REACH (1907/2006) - Article 59(1)	EU - REACH (1907/2006) - Endocrine
	- Candidate List of Substances of Very	Disruptor Assessment List of
	High Concern (SVHC) for Authorisation	Substances
Kerosine : distillates, hydrotreated light (D94/69	-	-
p1249) 4		

## **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
Kerosine : distillates, hydrotreated light (D94/69 p1249) 4 64742-47-8	80 - 100	-	265-149-8	Asp. Tox. 1 (H304)			

Full text of H- and EUH-phrases: see section 16

EGHS / EN Page 3/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

#### **Acute Toxicity Estimate**

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50 - 4	Inhalation LC50 - 4	Inhalation LC50 - 4
	mg/kg	mg/kg	hour - dust/mist - mg/L	hour - vapour - mg/L	hour - gas - ppm
Kerosine: distillates, hydrotreated light (D94/69 p1249) 4 64742-47-8	5000	2000	No data available	No data available	No data available

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

**Inhalation** Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed

pulmonary edema may occur.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person.

Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct

contact with skin. Use barrier to give mouth-to-mouth resuscitation.

EGHS / EN Page 4/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors**Because of the danger of aspiration, emesis or gastric lavage should not be used unless

the risk is justified by the presence of additional toxic substances.

### **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

**Unsuitable extinguishing media**Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

EGHS / EN Page 5/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 µg/g (0.0050 wt%) in Kerosene

\_\_\_\_\_

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

**Methods for containment**Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with

sprinklers. Use according to package label instructions.

General hygiene considerations Contaminated work clothing should not be allowed out of the workplace. Regular cleaning

of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

Wear suitable gloves and eye/face protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Please refer to the manufacturer's

EGHS / EN Page 6/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

\_\_\_\_\_

certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Exposure Limits**

Chemical name	France	Germany	Germany MAK	Greece	Hungary
Kerosine : distillates,	-	-	TWA: 5 mg/m <sup>3</sup>	-	-
hydrotreated light			TWA: 50 ppm		
(D94/69 p1249) 4			TWA: 350 mg/m <sup>3</sup>		
64742-47-8			Peak: 20 mg/m <sup>3</sup>		
			Peak: 700 mg/m <sup>3</sup>		
Chemical name	S	weden	Switzerland	Un	ited Kingdom
Kerosine : distillates,		-	TWA: 50 ppm		-
hydrotreated light (D94,	/69		TWA: 350 mg/m <sup>3</sup>		
p1249) 4		TWA: 5 mg/m <sup>3</sup>			
64742-47-8			STEL: 100 ppm		
			STEL: 700 mg/n	n <sup>3</sup>	

### **Biological occupational exposure limits**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL)
Predicted No Effect Concentration
(PNEC)

No information available. No information available.

8.2. Exposure controls

Personal protective equipment

**Eye/face protection** Tight sealing safety goggles. Avoid contact with eyes. Wear safety glasses with side shields

(or goggles).

EGHS / EN Page 7/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

Wear suitable gloves. Impervious gloves. Wear protective nitrile rubber gloves. The Hand protection

protective gloves to be used must comply with the specifications of EC Directive

89/686/EEC and the related standard EN374.

Skin and body protection Long sleeved clothing. Chemical resistant apron. Antistatic boots. Wear suitable protective

clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Contaminated work clothing should not be allowed out of the workplace. Regular cleaning General hygiene considerations

of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

Wear suitable gloves and eye/face protection.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Liquid **Appearance** Colour colourless Odour Characteristic.

**Odour threshold** No information available

Remarks • Method Property Values

Melting point / freezing point No data available None known No data available Initial boiling point and boiling None known

range

**Flammability** No data available None known None known

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point None known **Autoignition temperature** No data available None known None known

**Decomposition temperature** No data available None known

pH (as aqueous solution) No information available No data available Kinematic viscosity No data available None known

EGHS / EN Page 8 / 17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

### VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

Dynamic viscosity No data available None known Water solubility No data available None known Solubility(ies) No data available None known **Partition coefficient** No data available None known No data available Vapour pressure None known Relative density No data available None known No data available **Bulk density** 

Liquid Density No data available No data available

Relative vapour density No data available None known

**Particle characteristics** 

Particle Size No information available Particle Size Distribution No information available

#### 9.2. Other information

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

### SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** No information available.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical impact None. Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks.

10.5. Incompatible materials

**Incompatible materials**None known based on information supplied.

EGHS / EN Page 9/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

\_\_\_\_\_

Hazardous decomposition products None known based on information supplied.

## SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Information on likely routes of exposure

**Product Information** 

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal.

**Eye contact** Specific test data for the substance or mixture is not available.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

**Acute toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 2,002.80 mg/kg

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kerosine : distillates, hydrotreated light (D94/69 p1249) 4	> 5000 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L (Rat)4 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Based on available data, the classification criteria are not met.

EGHS / EN Page 10/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

Serious eye damage/eye irritation No information available.

**Respiratory or skin sensitisation** No information available.

Germ cell mutagenicity No information available.

**Carcinogenicity** No information available.

Reproductive toxicity No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects No information available.

## **SECTION 12: Ecological information**

12.1. Toxicity

**Ecotoxicity** The environmental impact of this product has not been fully investigated.

**Unknown aquatic toxicity**Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name Algae/aqua	tic plants Fish	Toxicity to	Crustacea
--------------------------	-----------------	-------------	-----------

EGHS / EN Page 11/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

			microorganisms	
Kerosine : distillates,	-	LC50: =2.2mg/L (96h,	-	-
hydrotreated light		Lepomis macrochirus)		
(D94/69 p1249) 4		LC50: =2.4mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: =45mg/L (96h,		
		Pimephales promelas)		

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

**Bioaccumulation** No information available.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment	
Kerosine: distillates, hydrotreated light (D94/69 p1249) 4	The substance is not PBT / vPvB	

### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

EGHS / EN Page 12/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

## **SECTION 14: Transport information**

IATA

14.1 UN number or ID number UN1223

14.2 UN proper shipping name Kerosene mixture

14.3 Transport hazard class(es) 3
14.4 Packing group

**Description** UN1223, Kerosene mixture, 3, III

**14.5 Environmental hazards** Not applicable

14.6 Special precautions for user

Special Provisions A324 ERG Code 3L

<u>IMDG</u>

14.1 UN number or ID number UN1223

**14.2 UN proper shipping name** Kerosene mixture

14.3 Transport hazard class(es) 3 14.4 Packing group

**Description** UN1223, Kerosene mixture, 3, III, (58°C c.c.)

14.5 Marine pollutant NP

14.6 Special precautions for user

Special Provisions Non

**EmS-No** F-E, S-E No information available

14.7 Maritime transport in bulk No information available according to IMO instruments

BID

14.1 UN number or ID number UN1223

14.2 UN proper shipping name Kerosene mixture

14.3 Transport hazard class(es)14.4 Packing group

**Description** UN1223, Kerosene mixture, 3, III

14.5 Environmental hazards Not applicable

14.6 Special precautions for user

**Special Provisions** None **Classification code** F1

<u>ADR</u>

**14.1 UN number or ID number** UN1223

**14.2 UN proper shipping name** Kerosene mixture

14.3 Transport hazard class(es) 3 14.4 Packing group

**Description** UN1223, Kerosene mixture, 3, III, (D/E)

**14.5 Environmental hazards** Not applicable

14.6 Special precautions for user

EGHS / EN Page 13/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

Special Provisions 664
Classification code F1
Tunnel restriction code (D/E)

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

#### **France**

Occupational Illnesses (R-463-3, France)

occupational inflocus (it iso o, i railes)		
Chemical name	French RG number	Title
Kerosine: distillates, hydrotreated light (D94/69	RG 84	-
p1249) 4		
64742-47-8		

Water hazard class (WGK)

slightly hazardous to water (WGK 1)

Poland

SDS created according to the following Polish regulation: Act of February 25, 2011 on chemical substances and their mixtures (Journal of Laws of 2018, item 143, as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing the European Chemicals Agency (EC) as amended. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, as amended. Regulation of the Minister of Health of 10 August 2012 on the criteria and method of classifying chemical substances and their mixtures (Journal of Laws of 2012, item 1018). Regulation of the Minister of Health of 20 April 2012 on labeling packaging of hazardous substances and mixtures and some mixtures (Journal of Laws of 2012, item 445). Regulation of the Minister of Family, Labor and Social Policy of 12 June 2018 on the maximum allowable concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286). Announcement of the Minister of Economy, Labor and Social Policy of August 28, 2003 on the publication of the unified text of the Ordinance of the Minister of Labor and Social Policy on general health and safety at work regulations (Journal of Laws of 2003, No. 169, item 1650). Regulation of the Minister of Health of 30 December 2004 on occupational safety and health related to the presence of chemical agents in the workplace (Journal of Laws of 2005, No. 11, item 86). Act of December 14, 2012 on waste (Journal of Laws of 2013, item 21) Regulation of the Minister of Health of December 30, 2004 on occupational health and safety related to the presence of chemical agents in the workplace (Journal U. of 2005, No. 11, item 86). Waste Act of December 14, 2012 (Journal of Laws of 2013, item 21). Act of 13 June 2013 on the management of packaging and packaging waste, Journal of Laws 2013, item 888).

EGHS / EN Page 14/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

\_\_\_\_\_\_

Government statement of September 24, 2002 - European Agreement on the International Carriage of Dangerous Goods by Road (ADR) (Journal of Laws No. 194, item 1629 and Journal of Laws of 2003, No. 207, item 2013 and 2014).

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

#### Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

#### **DIRECTIVE (EU) 2021/1187 on the marketing and use of explosives precursors** Not applicable

## **Persistent Organic Pollutants**

Not applicable

#### Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **International Inventories**

Contact supplier for inventory compliance status **TSCA DSL/NDSL** Contact supplier for inventory compliance status **EINECS/ELINCS** Contact supplier for inventory compliance status Contact supplier for inventory compliance status **ENCS** Contact supplier for inventory compliance status **IECSC** Contact supplier for inventory compliance status **KECL PICCS** Contact supplier for inventory compliance status Contact supplier for inventory compliance status **AIIC** 

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

EGHS / EN Page 15/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 μg/g (0.0050 wt%) in Kerosene

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

Chemical Safety Report A Chemical Safety Assessment has been carried out for this substance

### **SECTION 16: Other information**

Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H304 - May be fatal if swallowed and enters airways

#### Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

01:66	
Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

EGHS / EN Page 16/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 15-Mar-2022 Revision Number 1

VHG-SKERO-50-100 - Sulfur Standard: S @ 50 µg/g (0.0050 wt%) in Kerosene

#### Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications

Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date

15-Mar-2022

# This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006 Disclaimer

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise when using, handling and/ or storing the material. The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. LGC makes no warranties or representations as to the accuracy and completeness of the information contained herein, shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.

**End of Safety Data Sheet** 

EGHS / EN Page 17/17