

# REFERENCE MATERIAL CERTIFICATE

# ISO 17034

# **Reference Material**

This certificate is designed in accordance with ISO 17034 and ISO Guide 31. This reference material (RM) was designed, produced and verified in accordance with ISO/IEC 17025, ISO 17034 and a registered quality management system ISO 9001.

# **Product Name**

2-Ethylhexyl 4-methoxycinnamate

Product Code
DRE-C13342000

**CAS No**. 5466-77-3


Mol. Weight 290.40

Mol. Formula  $C_{18}H_{26}O_3$ 

Lot Number G1057969 Format Neat

Expiry Date 28 Feb 2024

Storage Temp  $4^{\circ}C \pm 4^{\circ}C$ 



# **CERTIFIED** Purity 99.43% (g/g)



# Uncertainty

The certified value(s) and uncertainty(ies) are determined in accordance with ISO 17034 with an 95% confidence level (k=2). Uncertainty is based on the Total Combined Uncertainty, including uncertainties of characterisation, homogeneity and stability testing. Stability values are based on real evidence opposed to simulation.


The producer certifies that this reference material meets the specification stated in this certificate until the expiry date, provided it is stored unopened at the recommended temperature herein. Product warranties for this reference material are set out in the terms and conditions of purchase.

CERTIFIED BY CERTIFIED OF		
D. Schmid 28 Feb 2020	D. Salmid	RM Release

# **DR EHRENSTORFER**<sup>™</sup>

# REFERENCE MATERIAL CERTIFICATE

# ISO 17034



#### Instrument HPLC/DAD

Column

ReproSil 100 C18 5 µm 250 x 3 mm

## Method Details

Eluent A: 100% Acetonitrile				
Eluent B: 100% Water				
Time [min]	Eluent A [%]	Eluent B [%]		
0	10	90		
1	10	90		
20	100	0		
25	100	0		

Flow 1 mL/min

# Method of Characterisation

Purity = 100% – Assay impurities – Water content (KF)

## Method of Identification

EA, NMR, RT, UV, IR, MS

#### **Batch Information**

Water Content: 0.10% (g/g) by Karl-Fischer-Titration (U(exp) = 0.18% (g/g)). Mixture of Isomers. Ratio unknown.

#### Intended Use

This RM is intended for use in a laboratory as a calibration and quality control standard or in method development for analytical techniques.

#### Safety

Proper precautions should be observed while handling. See Safety Data Sheet.

# Traceability

The balances used for gravimetric measurements are calibrated with weights traceable to the national standards (DKD). The calibration of

## LGC Labor GmbH

Bgm.-Schlosser-Straße 6A 86199 Augsburg, Germany T | +49 821 906080 F | +49 821 9060888 E | dr.ehrenstorfer@lgcgroup.com the balances is verified daily internally and annually by an external accredited calibration service. Chromatographic methods are traceable to the International System of Units (SI).

#### Homogeneity

Random replicate samples of the final packaged RM have been analysed to prove homogeneity compliant with ISO 17034.

## Storage

The RM should be stored in the original sealed container at the indicated temperature.

#### Instructions for use

It is recommended to use 1 mg as the minimum sample size and if less material is used, to increase the certified uncertainty by a factor of two for half sample and four for a quarter of sample. If storage after opening is necessary, the RM should be tightly closed and kept from light and moisture. If the RM was in a sealed ampoule, it should be transferred to a vial with minimum head space. Visit the support section of our website lgcstandards.com for a series of Dr. Ehrenstorfer Tech Tip videos and frequently asked questions.

LGC Labor GmbH is accreditated by DAkkS accreditation numbers D-RM-19883-01-00 & D-PL-19883-01-00 on ISO 17034:2017 & ISO/IEC 17025:2018

