



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Code(s)	DRE-XA14920000TO
Product Name	Metalaxyl 100 µg/mL in Toluene
Form	Not applicable
EC No (EU Index No)	-
CAS No.	-
Unique Formula Identifier (UFI)	0ETW-1082-D00K-9WUD
Pure substance/mixture	Mixture
Formula	-
Molecular weight	-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Laboratory use
Uses advised against	No information available

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

LGC Limited  
Queens Road  
Teddington  
Middlesex TW11 0LY  
UNITED KINGDOM  
:+44 (0) 20 8943 7000  
Fax :+44 (0) 20 8943 2767  
eMail : gb@lgcstandards.com

Web : [www.lgcstandards.com](http://www.lgcstandards.com)

For further information, please contact

**E-mail address** sds-request@lgcgroup.com



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

## 1.4. Emergency telephone number

Emergency Telephone

For Hazardous Materials or Dangerous Goods Incident  
Spill, Leak, Fire Exposure, or Accident  
Call CHEMTREC:  
USA & Canada 1-800-424-9300  
Rest of the world +1 703-741-3877

Emergency Telephone - §45 - (EC)1272/2008	
Europe	112
Austria	No information available
Bulgaria	
Croatia	
Cyprus	
Czech Republic	
Denmark	
France	
Hungary	
Ireland	
Italy	
Lithuania	
Luxembourg	
Netherlands	
Norway	
Portugal	
Romania	
Slovakia	
Slovenia	
Spain	
Sweden	
Switzerland	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to  
Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Reproductive toxicity	Category 2 - (H361d)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Flammable liquids	Category 2 - (H225)

## 2.2. Label elements

203-625-9  
Contains Toluene



Signal word  
Danger

## Hazard statements

H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H225 - Highly flammable liquid and vapour  
EUH208 Contains metalaxyl (ISO) May produce an allergic reaction.

## Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P331 - Do NOT induce vomiting  
P370 + P378 - In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam to extinguish  
P403 + P235 - Store in a well-ventilated place. Keep cool

## 2.3. Other hazards

No information available.

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

Chemical name	EU - REACH (1907/2006) - Article 59(1) - Candidate List of Substances of Very	EU - REACH (1907/2006) - Endocrine Disruptor Assessment List of
---------------	----------------------------------------------------------------------------------	--------------------------------------------------------------------



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

	High Concern (SVHC) for Authorisation	Substances
Toluene	-	-
metalaxyl (ISO)	-	-

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

**Chemical nature** Mixture of organic compounds.

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
Toluene 108-88-3	80 - 100	-	203-625-9	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)			
metalaxyl (ISO) 57837-19-1	0.1 - 1	-	260-979-7	Acute Tox. 4 (H302) Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)			

#### Full text of H- and EUH-phrases: see section 16

#### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Toluene 108-88-3	2600	12000	12.5	No data available	No data available
metalaxyl (ISO) 57837-19-1	669	6000	No data available	No data available	No data available



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Inhalation</b>	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Large Fire** CAUTION: Use of water spray when fighting fire may be inefficient.

**Unsuitable extinguishing media** Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

	or other non-combustible material and transfer to containers for later disposal.
<b>Methods for cleaning up</b>	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
<b>Prevention of secondary hazards</b>	Clean contaminated objects and areas thoroughly observing environmental regulations.
<b>6.4. Reference to other sections</b>	
<b>Reference to other sections</b>	See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

<b>Advice on safe handling</b>	Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.
<b>General hygiene considerations</b>	Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

<b>Storage Conditions</b>	Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.
---------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 7.3. Specific end use(s)



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> STEL 100 ppm STEL 380 mg/m <sup>3</sup> Sk*	TWA: 20 ppm TWA: 77 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 192.0 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384.0 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 200 mg/m <sup>3</sup> Sk* Ceiling: 500 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 94 mg/m <sup>3</sup> STEL: 384 mg/m <sup>3</sup> STEL: 100 ppm Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 25 ppm TWA: 81 mg/m <sup>3</sup> STEL: 100 ppm STEL: 380 mg/m <sup>3</sup> Sk*
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
Toluene 108-88-3	TWA: 20 ppm TWA: 76.8 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> Peak: 100 ppm Peak: 380 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 190 mg/m <sup>3</sup> TWA: 50 ppm STEL: 384 mg/m <sup>3</sup> STEL: 100 ppm Sk*
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
Toluene 108-88-3	TWA: 192 mg/m <sup>3</sup> TWA: 50 ppm STEL: 384 mg/m <sup>3</sup> STEL: 100 ppm Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> Sk*	TWA: 20 ppm TWA: 75.4 mg/m <sup>3</sup>	TWA: 14 ppm TWA: 50 mg/m <sup>3</sup> STEL: 40 ppm STEL: 150 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 39 ppm TWA: 150 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 94 mg/m <sup>3</sup> STEL: 37.5 ppm STEL: 141 mg/m <sup>3</sup> Sk*	TWA: 100 mg/m <sup>3</sup> STEL: 200 mg/m <sup>3</sup> Sk*
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> Sk* Ceiling: 384 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>





# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

Chemical name	Sweden	Switzerland	United Kingdom
Toluene 108-88-3	NGV: 50 ppm NGV: 192 mg/m <sup>3</sup> Bindande KGV: 100 ppm Bindande KGV: 384 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> STEL: 200 ppm STEL: 760 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 191 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*

### Biological occupational exposure limits

Chemical name	European Union	Austria	Bulgaria	Croatia	Czech Republic
Toluene 108-88-3	-	Check 10 g/dL Hemoglobin (blood - by the first screening and once yearly) 12 g/dL Hemoglobin (blood - by the first screening and once yearly) 3.2 million/µL Erythrocytes (blood - by the first screening and once yearly) 3.8 million/µL Erythrocytes (blood - by the first screening and once yearly) 4000 Leukocytes/µL (blood - by the first screening and once yearly) 13000 Leukocytes/µL (blood - by the first screening and once yearly) 130000 Thrombocytes/µL (blood - by the first screening and once yearly) 150000 Thrombocytes/µL	1.6 mmol/mmol Creatinine - urine (Hippuric acid) - at the end of exposure or end of work shift	1.0 mg/L - blood (Toluene) - at the end of the work shift 20 ppm - final exhaled air (Toluene) - during exposure 2.50 g/g Creatinine - urine (Hippuric acid) - at the end of the work shift 1.0 mg/g Creatinine - urine (o-Cresol) - at the end of the work shift	1.6 µmol/mmol Creatinine (urine - o-Cresol end of shift) 1000 µmol/mmol Creatinine (urine - Hippuric acid end of shift) 1.5 mg/g Creatinine (urine - o-Cresol end of shift) 1600 mg/g Creatinine (urine - Hippuric acid end of shift)



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

		(blood - by the first screening and once yearly) 0.8 mg/L (urine - o-Cresol after end of work day, at the end of a work week/end of the shift)			
Chemical name	Denmark	Finland	France	Germany DFG	Germany TRGS
Toluene 108-88-3	-	500 nmol/L (blood - Toluene in the morning after a working day)	20 µg/L - blood (Toluene) - end of workweek - urine (Hippuric acid) - end of shift	600 µg/L (whole blood - Toluene immediately after exposure) 75 µg/L (urine - Toluene end of shift) 1.5 mg/L (urine - o-Cresol (after hydrolysis) for long-term exposures: at the end of the shift after several shifts) 1.5 mg/L (urine - o-Cresol (after hydrolysis) end of shift) 600 µg/L - BAT (immediately after exposure) blood 75 µg/L - BAT (end of exposure or end of shift) urine 1.5 mg/L - BAT (end of exposure or end of shift) urine	600 µg/L (whole blood - Toluene immediately after exposure) 75 µg/L (urine - Toluene end of shift) 1.5 mg/L (urine - o-Cresol (after hydrolysis) for long-term exposures: at the end of the shift after several shifts) 1.5 mg/L (urine - o-Cresol (after hydrolysis) end of shift)
Chemical name	Hungary	Ireland	Italy MDLPS	Italy AIDII	
Toluene 108-88-3	1 mg/g Creatinine (urine - o-Cresol end of shift) 1 µmol/mmol Creatinine (urine - o-Cresol end of shift)	0.02 mg/L (blood - Toluene prior to last shift of workweek) 0.03 mg/L (urine - Toluene end of shift) 0.3 mg/g Creatinine (urine - o-Cresol end of shift)	-	0.3 mg/g Creatinine - urine (o-Cresol (with hydrolysis)) - end of shift 0.03 mg/L - urine (Toluene) - end of shift 0.02 mg/L - blood (Toluene) - prior to last shift of workweek	
Chemical name	Latvia	Luxembourg	Romania	Slovakia	
Toluene	1.6 g/g Creatinine - urine	-	2 g/L - urine (Hippuric	600 µg/L (blood - Toluene	



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

108-88-3	(Hippuric acid) - end of shift 0.05 mg/L - blood (Toluene) - end of shift		acid) - end of shift 3 mg/L - urine (o-Cresol) - end of shift	end of exposure or work shift) 1.5 mg/L (urine - o-Cresol after all work shifts) 1.5 mg/L (urine - o-Cresol end of exposure or work shift) 1600 mg/g creatinine ( - Hippuric acid end of exposure or work shift)
Chemical name	Slovenia	Spain	Switzerland	United Kingdom
Toluene 108-88-3	600 µg/L - blood (Toluene) - immediately after exposure 1.5 mg/L - urine (o-Cresol (after hydrolysis)) - at the end of the work shift; for long-term exposure: at the end of the work shift after several consecutive workdays 75 µg/L - urine (Toluene) - at the end of the work shift	0.6 mg/L (urine - o-Cresol end of shift) 0.05 mg/L (blood - Toluene start of last shift of workweek) 0.08 mg/L (urine - Toluene end of shift)	600 µg/L (whole blood - Toluene end of shift) 6.48 µmol/L (whole blood - Toluene end of shift) 2 g/g creatinine (urine - Hippuric acid end of shift, and after several shifts (for long-term exposures)) 1.26 mmol/mmol creatinine (urine - Hippuric acid end of shift, and after several shifts (for long-term exposures)) 0.5 mg/L (urine - o-Cresol end of shift, and after several shifts (for long-term exposures)) 4.62 µmol/L (urine - o-Cresol end of shift, and after several shifts (for long-term exposures)) 75 µg/L (urine - Toluol end of shift)	-

**Derived No Effect Level (DNEL)** No information available.  
**Predicted No Effect Concentration (PNEC)** No information available.

## 8.2. Exposure controls

### Personal protective equipment

**Eye/face protection** Avoid contact with eyes. Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

## Hand protection

Wear protective Viton™ gloves. The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374. Wear suitable gloves. Impervious gloves.

Gloves			
Duration of contact	PPE - Glove material	Glove thickness	Break through time
	Wear protective Viton™ gloves		

## Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

## Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

## General hygiene considerations

Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

## Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Colour	colourless
Odour	Aromatic.
Odour threshold	No information available

Property	Values	Remarks • Method
Melting point / freezing point	-95 °C	None known
Initial boiling point and boiling range	110.6 °C	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	7.8 Vol% - 300 g/m <sup>3</sup>	
Lower flammability or explosive limits	1% - 39 g/m <sup>3</sup>	
Flash point	4 °C	None known



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

Autoignition temperature	535 °C	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	No information available
Kinematic viscosity	No data available	None known
Dynamic viscosity	0.6 mPa s	@ 20°C
Water solubility	520 mg/L	None known
Solubility(ies)	No data available	None known
Partition coefficient	2.7	None known
Vapour pressure	29.1 hPa	@ 20°C
Relative density	0.87	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	3.18	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

### 9.2. Other information

Molecular weight	-
Molecular formula	-

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.  
Sensitivity to static discharge Yes.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

**DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene**

---

## 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks.

## 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None known based on information supplied.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### **Product Information**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. May cause irritation.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Numerical measures of toxicity

**Acute toxicity**



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	99,999.00 mg/kg
ATEmix (dermal)	99,999.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-dust/mist)	99,999.00 mg/l
ATEmix (inhalation-vapour)	99,999.00 mg/l

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
metalaxyl (ISO)	= 566 mg/kg ( Rat )	> 3100 mg/kg ( Rabbit )	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitisation	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Toluene	Repr. 2

STOT - single exposure May cause drowsiness or dizziness.



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

**Unknown aquatic toxicity** Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Toluene	EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata) EC50: >433mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h, Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata)	-	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)





# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

		LC50: 50.87 - 70.34mg/L (96h, <i>Poecilia reticulata</i> )		
metalaxyl (ISO)	-	LC50: 13.6 - 30.8mg/L (96h, <i>Oncorhynchus mykiss</i> ) LC50: 23 - 30mg/L (96h, <i>Lepomis macrochirus</i> ) LC50: >100mg/L (96h, <i>Cyprinus carpio</i> ) LC50: >100mg/L (96h, <i>Poecilia reticulata</i> )	-	-

## 12.2. Persistence and degradability

Persistence and degradability No information available.

## 12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

### Component Information

Chemical name	Partition coefficient
Toluene	2.7
metalaxyl (ISO)	1.59

## 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Toluene	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

## 12.7. Other adverse effects

No information available.



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

## SECTION 14: Transport information

### IATA

14.1 UN number or ID number	UN1294
14.2 UN proper shipping name	Toluene mixture
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1294, Toluene mixture, 3, II
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	None
ERG Code	3L

### IMDG

14.1 UN number or ID number	UN1294
14.2 UN proper shipping name	Toluene mixture
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1294, Toluene mixture, 3, II, (4°C c.c.)
14.5 Marine pollutant	NP
Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	None
EmS-No.	F-E, S-D No information available
14.7 Maritime transport in bulk according to IMO instruments	No information available

### RID

14.1 UN number or ID number	UN1294
14.2 UN proper shipping name	Toluene mixture
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1294, Toluene mixture, 3, II
14.5 Environmental hazards	No



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

## 14.6 Special precautions for user

Special Provisions None  
Classification code F1

## ADR

14.1 UN number or ID number UN1294  
14.2 UN proper shipping name Toluene mixture  
14.3 Transport hazard class(es) 3  
14.4 Packing group II  
Description UN1294, Toluene mixture, 3, II, (D/E)  
14.5 Environmental hazards No  
14.6 Special precautions for user  
Special Provisions None  
Classification code F1  
Tunnel restriction code (D/E)

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

##### France

##### Occupational Illnesses (R-463-3, France)

Chemical name	French RG number	Title
Toluene 108-88-3	RG 4bis, RG 84	-

##### Germany

Water hazard class (WGK) strongly hazardous to water (WGK 3)

##### Netherlands

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Carcinogens	Netherlands - List of Reproductive Toxins
Toluene	-	-	Development Category 2

##### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

### Authorisations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

### DIRECTIVE (EU) 2021/1187 on the marketing and use of explosives precursors

Not applicable

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Toluene - 108-88-3	48 75	

### Persistent Organic Pollutants

Not applicable

### Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

### EU - Plant Protection Products (1107/2009/EC)

Chemical name	EU - Plant Protection Products (1107/2009/EC)
metalaxyl (ISO) - 57837-19-1	Plant protection agent

### International Inventories

#### TSCA

LGC has not confirmed that the chemical substances in this product are on the TSCA Inventory, and LGC is distributing this product solely for use either in applications statutorily exempt from TSCA and regulated under other laws (e.g., FFDCa, FIFRA) or in research and development activities in accordance with the TSCA Inventory R&D exemption provided at 40 CFR 720.36. It is the end-user's responsibility to understand and follow the requirements that apply to its use of this product.

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

#### DSL/NDL

#### EINECS/ELINCS

#### ENCS

#### IECSC

#### KECL

#### PICCS

#### AIIC



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

**DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene**

## Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

## 15.2. Chemical safety assessment

### **Chemical Safety Report**

A Chemical Safety Assessment is not required for this substance

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

H225 - Highly flammable liquid and vapour  
H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects

#### **Legend**

SVHC: Substances of Very High Concern for Authorisation:

#### **Legend Section 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

## DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene

Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable liquids	On basis of test data

### Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)  
U.S. Environmental Protection Agency ChemView Database  
European Food Safety Authority (EFSA)  
EPA (Environmental Protection Agency)  
Acute Exposure Guideline Level(s) (AEGL(s))  
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
U.S. Environmental Protection Agency High Production Volume Chemicals  
Food Research Journal  
Hazardous Substance Database  
International Uniform Chemical Information Database (IUCLID)  
Japan GHS Classification  
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
NIOSH (National Institute for Occupational Safety and Health)  
National Library of Medicine's ChemID Plus (NLM CIP)  
National Library of Medicine's PubMed database (NLM PUBMED)  
National Toxicology Program (NTP)  
New Zealand's Chemical Classification and Information Database (CCID)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set  
World Health Organization

Revision date 08-Oct-2024

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

### Disclaimer

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 08-Oct-2024

Revision Number 1

**DRE-XA14920000TO - Metalaxyl 100 µg/mL in Toluene**

---

when using, handling and/ or storing the material. The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. LGC makes no warranties or representations as to the accuracy and completeness of the information contained herein, shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.

**End of Safety Data Sheet**