

REFERENCE MATERIAL CERTIFICATE

ISO 17034

Certified Reference Material

This certificate is designed in accordance with ISO 17034 and ISO Guide 31. This certified reference material (CRM) was designed, produced and verified in accordance with ISO/IEC 17025, ISO 17034 and a registered quality management system ISO 9001.

Product Name

Disperse Yellow 3 D3 100 µg/mL in Acetonitrile

Product Code Lot Number
DRE-XA12972311AL H1465220AL

CAS No. Format 947601-96-9 Solution

Mol. Weight Expiry Date 272.32 26 Jun 2030

 $\begin{array}{ll} \mbox{Mol. Formula} & \mbox{Storage Temp} \\ \mbox{C_{15}D_3$H}_{12}\mbox{$N_3$O}_2 & 20^{\circ}\mbox{$C$} \pm 4^{\circ}\mbox{$C$} \end{array}$

	но	
2H 2H	N	

CERTIFIED

Concentration 99.93 µg/mL

CERTIFIED

Expanded Uncertainty (U) 5.00 µg/mL

Uncertainty

The certified value(s) and uncertainty(ies) are determined in accordance with ISO 17034 with an 95% confidence level (k=2). Uncertainty is based on the Total Combined Uncertainty, including uncertainties of preparation, purity of neat materials, homogeneity and stability testing. Stability values are based on real evidence opposed to simulation.


The producer certifies that this certified reference material meets the specification stated in this certificate until the expiry date, provided it is stored unopened at the recommended temperature herein. Product warranties for this certified reference material are set out in the terms and conditions of purchase.

CERTIFIED BY	CERTIFIED ON		
T. Erz	26 Jun 2024	Tama	RM Release



REFERENCE MATERIAL CERTIFICATE

ISO 17034



Instrument

UHPLC/DAD

Column

LUNA Omega C18 1.6 μm 100 x 2.1 mm

Method Details

Eluent A: 100% Acetonitrile Eluent B: Water + H3PO4

Time [min]	Eluent A [%]	Eluent B [%]			
0	10	90			
0.3	10	90			
8	98	2			
9.5	98	2			

Flow

0.5 mL/min

Method of Preparation

The certified value is based on gravimetric and volumetric preparation of this CRM. This CRM has been confirmed by the appropriate analytical techniques.

Batch Information

Solvent: Acetonitrile, Lot No. M304M82, 40.00 mL.

Concentration calculation based on Combined Purity = Chemical Purity * Isotopic Value.

Gravimetric Data

Compound Name	Lot No.	Combined Purity (%)	- 2	Chemical Purity (%)	Isotopic Purity (%)
Disperse Yellow 3 D3	1465219	98.7	4.050	99.9	98.8

Intended Use

This CRM is intended for use in a laboratory as a calibration and quality control standard or in method development for analytical techniques.

Safety

Proper precautions should be observed while handling. See Safety Data Sheet.

Traceability

The balances used for gravimetric measurements are calibrated with weights traceable to the national standards (DKD). The calibration of

the balances is verified daily internally and annually by an external accredited calibration service.
Chromatographic methods are traceable to the International System of Units (SI).

Homogeneity

Random replicate samples of the final packaged CRM have been analysed to prove homogeneity compliant with ISO 17034.

Storage

The CRM should be stored in the original sealed container at the indicated temperature.

Instructions for use

The CRM should be used shortly after opening to avoid concentration changes due to evaporation. It is recommended to use 1 mL as the minimum sample size and if less material is used, to increase the certified uncertainty by a factor of two for half sample and four for a quarter of sample. If storage after opening is necessary, the CRM should be tightly closed and kept from light and moisture. If the CRM was in a sealed ampoule, it should be transferred to a vial with minimum head space. Visit the support section of our website lgcstandards.com for a series of Dr. Ehrenstorfer Tech Tip videos and frequently asked questions.

LGC Labor GmbH

Bgm.-Schlosser-Straße 6A 86199 Augsburg, Germany T | +49 821 906080 F | +49 821 9060888

 ${\sf E}\mid dr. ehrenstor fer@lgcgroup.com$

LGC Labor GmbH is accredited by DAkkS as reference material producer on ISO 17034 (D-RM-19883-01-00).

All characterisation measurements at LGC Labor GmbH are accredited methods to ISO/IEC 17025.

