

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) VHG-SDSL-2500-100

Product Name Sulfur Standard: S @ 2500 µg/g (0.2500 wt%) in Diesel

Unique Formula Identifier (UFI) 95AG-V4M7-U00E-YKSQ

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Laboratory use

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Supplier

LGC Limited Queens Road Teddington Middlesex TW11 0LY UNITED KINGDOM :+44 (0) 20 8943 7000 Fax :+44 (0) 20 8943 2767 eMail : gb@lgcstandards.com

Web: www.lgcstandards.com

For further information, please contact

E-mail address sds-request@lgcgroup.com

1.4. Emergency telephone number

Emergency Telephone For Hazardous Materials or Dangerous Goods Incident

Spill, Leak, Fire Exposure, or Accident

Call CHEMTREC:

USA & Canada 1-800-424-9300 Rest of the world +1 703-741-5970

Emergency Telephone - §45 - (EC)1	272/2008
Europe	112

EGHS / EN Page 1/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Number 1

Revision date 09-Sep-2022

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

Austria No information available Bulgaria Croatia Cyprus Czech Republic Denmark France Hungary Ireland Italy Lithuania (+352) 8002 5500 Free telephone number with a 24/7 access in French, Dutch and English. Luxembourg Netherlands Norway Portugal Romania Slovakia Slovenia Spain Sweden Switzerland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Gasoil: fuels, diesel, nr 2

EGHS / EN Page 2/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Number 1

Revision date 09-Sep-2022

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel



Signal word Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H332 - Harmful if inhaled

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H226 - Flammable liquid and vapour

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish

P391 - Collect spillage

P403 + P235 - Store in a well-ventilated place. Keep cool

2.3. Other hazards

No information available.

Chemical name	EU - REACH (1907/2006) - Article 59(1)	EU - REACH (1907/2006) - Endocrine
	- Candidate List of Substances of Very	Disruptor Assessment List of
	High Concern (SVHC) for Authorisation	Substances
Gasoil : fuels, diesel, nr 2	-	-

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

EGHS / EN Page 3/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

3.2 Mixtures

Chemical name	Weight-%	REACH registration	EC No	Classification according	Specific	M-Factor	M-Factor
		number		to Regulation (EC) No.	concentration		(long-term)
				1272/2008 [CLP]	limit (SCL)		
Gasoil: fuels, diesel,	80 - 100	-	270-676-1	Flam. Liq. 3 (H226)			
nr 2				Acute Tox. 4 (H332)			
68476-34-6				Skin Irrit. 2 (H315)			
				Carc. 2 (H351)			
				STOT RE 2 (H373)			
				Asp. Tox. 1 (H304)			
				Aquatic Chronic 2			
				(H411)			

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate
No information available

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the

doctor in attendance. Immediate medical attention is required.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed

pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Get medical attention if irritation develops and persists.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person.

Get immediate medical advice/attention.

EGHS / EN Page 4/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Because of the danger of aspiration, emesis or gastric lavage should not be used unless the

risk is justified by the presence of additional toxic substances.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3. Advice for firefighters

Personal precautions

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

on resolutions, presente equipment and emergency presented

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing

EGHS / EN Page 5/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containmentStop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapours or mists. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient

ventilation, wear suitable respiratory equipment.

General hygiene considerations Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of

equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear

suitable gloves and eye/face protection.

EGHS / EN Page 6/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022

Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Gasoil : fuels, diesel, nr 2 68476-34-6	-	-	TWA: 100 mg/m ³	-	-
Chemical name	Ireland	Italy	Italy REL	Latvia	Lithuania
Gasoil : fuels, diesel, nr 2 68476-34-6	-	-	TWA: 100 mg/m ³	-	-
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Gasoil : fuels, diesel, nr 2 68476-34-6	TWA: 100 mg/m ³ P*	-	-	-	-

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL)
Predicted No Effect Concentration
(PNEC)

No information available. No information available.

(. .._0)

8.2. Exposure controls

EGHS / EN Page 7/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes. Wear safety glasses with side shields

(or goggles).

Wear suitable gloves. Impervious gloves. Wear protective nitrile rubber gloves. The Hand protection

protective gloves to be used must comply with the specifications of EC Directive

89/686/EEC and the related standard EN374.

Skin and body protection Long sleeved clothing. Chemical resistant apron. Antistatic boots. Wear suitable protective

clothing.

No protective equipment is needed under normal use conditions. If exposure limits are Respiratory protection

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of

> equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear

suitable gloves and eye/face protection.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** Liquid Colour vellow

Petroleum distillates. Odour **Odour threshold** No information available

Remarks • Method **Property** <u>Values</u>

Melting point / freezing point -40 - -6 °C Initial boiling point and boiling range150 - 180 °C None known None known Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

55 °C Flash point None known No data available **Autoignition temperature** None known

EGHS / EN Page 8 / 17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

No data available

No data available

Decomposition temperature

No data available No data available pH (as aqueous solution) Kinematic viscosity No data available No data available **Dynamic viscosity** Water solubility No data available Solubility(ies) No data available **Partition coefficient** No data available

4 hPa Vapour pressure Relative density 0.84 **Bulk density** No data available

Liquid Density Relative vapour density

Particle characteristics

Particle Size Distribution

None known None known

No information available

None known None known None known None known None known @ 40 °C None known

None known

No information available **Particle Size** No information available

9.2. Other information

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

EGHS / EN Page 9 / 17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 µg/g (0.2500 wt%) in Diesel

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness

and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 1.51 mg/l

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information

EGHS / EN Page 10/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022

Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 µg/g (0.2500 wt%) in Diesel

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Gasoil : fuels, diesel, nr 2	> 5000 mg/kg (Rat)	> 5 mL/kg (Rat)	4.1 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitisation No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union	
Gasoil : fuels, diesel, nr 2	Carc. 2	

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

EGHS / EN Page 11/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022

Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Unknown aquatic toxicityContains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment	
Gasoil : fuels, diesel, nr 2	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused Should not be released into the environment. Dispose of in accordance with local

EGHS / EN Page 12/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 µg/g (0.2500 wt%) in Diesel

products regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number UN1202

14.2 UN proper shipping name Diesel fuel mixture

14.3 Transport hazard class(es) 3
14.4 Packing group ||||

Description UN1202, Diesel fuel mixture, 3, III

14.5 Environmental hazards Yes

14.6 Special precautions for user

Special Provisions A3 ERG Code 3L

IMDG

14.1 UN number or ID number 14.2 UN proper shipping nameUN1202
Gas oil mixture

14.3 Transport hazard class(es) 3
14.4 Packing group

Description UN1202, Gas oil mixture, 3, III, (55°C c.c.), Marine pollutant

14.5 Marine pollutant P
Environmental hazards Yes

14.6 Special precautions for user

Special Provisions None

EmS-No F-E, S-E No information available

14.7 Maritime transport in bulk according to IMO instruments

No information available

RID

14.1 UN number or ID number UN1202

14.2 UN proper shipping name Diesel fuel mixture

14.3 Transport hazard class(es) 3 14.4 Packing group ||||

Description UN1202, Diesel fuel mixture, 3, III, Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special precautions for user

Special Provisions 640L **Classification code** F1

ADR

14.1 UN number or ID number UN1202

14.2 UN proper shipping name Diesel fuel mixture

EGHS / EN Page 13/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 µg/g (0.2500 wt%) in Diesel

14.3 Transport hazard class(es) 3
14.4 Packing group ||||

Description UN1202, Diesel fuel mixture, 3, III, (D/E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special precautions for user

Special Provisions 640L, 664
Classification code F1
Tunnel restriction code (D/E)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Germany

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Poland

SDS created according to the following Polish regulation: Act of February 25, 2011 on chemical substances and their mixtures (Journal of Laws of 2018, item 143, as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing the European Chemicals Agency (EC) as amended. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, as amended. Regulation of the Minister of Health of 10 August 2012 on the criteria and method of classifying chemical substances and their mixtures (Journal of Laws of 2012, item 1018). Regulation of the Minister of Health of 20 April 2012 on labeling packaging of hazardous substances and mixtures and some mixtures (Journal of Laws of 2012, item 445). Regulation of the Minister of Family, Labor and Social Policy of 12 June 2018 on the maximum allowable concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286). Announcement of the Minister of Economy, Labor and Social Policy of August 28, 2003 on the publication of the unified text of the Ordinance of the Minister of Labor and Social Policy on general health and safety at work regulations (Journal of Laws of 2003, No. 169, item 1650). Regulation of the Minister of Health of 30 December 2004 on occupational safety and health related to the presence of chemical agents in the workplace (Journal of Laws of 2005, No. 11, item 86). Act of December 14, 2012 on waste (Journal of Laws of 2013, item 21) Regulation of the Minister of Health of December 30, 2004 on occupational health and safety related to the presence of chemical agents in the workplace (Journal U. of 2005, No. 11, item 86). Waste Act of December 14, 2012 (Journal of Laws of 2013, item 21). Act of 13 June 2013 on the management of packaging and packaging waste, Journal of Laws 2013, item 888).

EGHS / EN Page 14/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 µg/g (0.2500 wt%) in Diesel

Government statement of September 24, 2002 - European Agreement on the International Carriage of Dangerous Goods by Road (ADR) (Journal of Laws No. 194, item 1629 and Journal of Laws of 2003, No. 207, item 2013 and 2014).

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

DIRECTIVE (EU) 2021/1187 on the marketing and use of explosives precursorsNot applicable

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

Contact supplier for inventory compliance status **TSCA** DSL/NDSL Contact supplier for inventory compliance status **EINECS/ELINCS** Contact supplier for inventory compliance status Contact supplier for inventory compliance status **ENCS** Contact supplier for inventory compliance status **IECSC KECL** Contact supplier for inventory compliance status **PICCS** Contact supplier for inventory compliance status AIIC Contact supplier for inventory compliance status

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

EGHS / EN Page 15/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 09-Sep-2022 Revision Number 1

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

Chemical Safety Report

A Chemical Safety Assessment has been carried out for this substance

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H332 - Harmful if inhaled

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method

EGHS / EN Page 16/17



This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Number 1

Revision date 09-Sep-2022

VHG-SDSL-2500-100 - Sulfur Standard: S @ 2500 μg/g (0.2500 wt%) in Diesel

STOT - single exposure

Acute aquatic toxicity

Calculation method

Chronic aquatic toxicity

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Ozone

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications

Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date

09-Sep-2022

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006 Disclaimer

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise when using, handling and/ or storing the material. The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. LGC makes no warranties or representations as to the accuracy and completeness of the information contained herein, shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.

End of Safety Data Sheet

EGHS / EN Page 17/17