



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) VHG-SDSL-5000-100
Product Name Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel
Unique Formula Identifier (UFI) 95AG-V4M7-U00E-YKSQ
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Laboratory use
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Supplier

LGC Limited
Queens Road
Teddington
Middlesex TW11 0LY
UNITED KINGDOM
:+44 (0) 20 8943 7000
Fax :+44 (0) 20 8943 2767
eMail : gb@lgcstandards.com

Web : www.lgcstandards.com

For further information, please contact

E-mail address sds-request@lgcgroup.com

1.4. Emergency telephone number

Emergency Telephone For Hazardous Materials or Dangerous Goods Incident
Spill, Leak, Fire Exposure, or Accident
Call CHEMTREC:
USA & Canada 1-800-424-9300
Rest of the world +1 703-741-5970

Emergency Telephone - §45 - (EC)1272/2008	
Europe	112
Austria	
Bulgaria	
Croatia	



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Cyprus	
Czech Republic	
Denmark	
France	
Hungary	
Ireland	
Italy	
Lithuania	
Luxembourg	
Netherlands	
Norway	
Portugal	
Romania	
Slovakia	
Slovenia	
Spain	
Sweden	
Switzerland	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Gasoil : fuels, diesel, nr 2



Signal word

Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

H332 - Harmful if inhaled
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects
H226 - Flammable liquid and vapour

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry chemical, CO₂, water spray or alcohol-resistant foam to extinguish
P391 - Collect spillage
P403 + P235 - Store in a well-ventilated place. Keep cool

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
Gasoil : fuels, diesel, nr 2 68476-34-6	80 - 100	-	270-676-1	Flam. Liq. 3 (H226) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Carc. 2 (H351) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411)			

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate
No information available



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
-------------------------------------	---



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
5.2. Special hazards arising from the substance or mixture	
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
5.3. Advice for firefighters	
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapours or mists.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA.

7.3. Specific end use(s)

Identified uses

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Gasoil : fuels, diesel, nr 2 68476-34-6	-	-	TWA: 100 mg/m ³ *	-	-
Chemical name	Ireland	Italy	Italy REL	Latvia	Lithuania
Gasoil : fuels, diesel, nr 2 68476-34-6	-	-	TWA: 100 mg/m ³ *	-	-
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Gasoil : fuels, diesel, nr 2 68476-34-6	TWA: 100 mg/m ³ P*	-	-	-	-

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Impervious gloves. Wear protective nitrile rubber gloves. The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374.

Skin and body protection Long sleeved clothing. Chemical resistant apron. Antistatic boots. Wear suitable protective clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Colour	yellow
Odour	Petroleum distillates.
Odour threshold	No information available

Property	Values	Remarks • Method
Melting point / freezing point	-40 - -6 °C	None known
Boiling point / boiling range	150 180 - °C	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	55 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	No information available
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	4 hPa	@ 40 °C
Relative density	0.84	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 1.51 mg/l

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Gasoil : fuels, diesel, nr 2	> 5000 mg/kg (Rat)	> 5 mL/kg (Rat)	4.1 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitisation No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Gasoil : fuels, diesel, nr 2	Carc. 2

Reproductive toxicity No information available.

STOT - single exposure No information available.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Gasoil : fuels, diesel, nr 2	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	UN1202
14.2 UN proper shipping name	Diesel fuel mixture
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1202, Diesel fuel mixture, 3, III
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	A3
ERG Code	3L

IMDG

14.1 UN number or ID number	UN1202
14.2 UN proper shipping name	Diesel fuel mixture
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1202, Diesel fuel mixture, 3, III, (55°C c.c.), Marine pollutant
14.5 Marine pollutant	P
Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	None
EmS-No	F-E, S-E No information available
14.7 Maritime transport in bulk according to IMO instruments	No information available

RID

14.1 UN number or ID number	UN1202
14.2 UN proper shipping name	Diesel fuel mixture
14.3 Transport hazard class(es)	3



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

14.4 Packing group	III
Description	UN1202, Diesel fuel mixture, 3, III, Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	640L
Classification code	F1
ADR	
14.1 UN number or ID number	UN1202
14.2 UN proper shipping name	Diesel fuel mixture
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1202, Diesel fuel mixture, 3, III, (D/E), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	640L, 664
Classification code	F1
Tunnel restriction code	(D/E)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Germany

Water hazard class (WGK) Obviously hazardous to water (WGK 2)

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

DIRECTIVE (EU) 2021/1187 on the marketing and use of explosives precursors

Not applicable

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS
E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009
Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status
DSL/NDSL	Contact supplier for inventory compliance status
EINECS/ELINCS	Contact supplier for inventory compliance status
ENCS	Contact supplier for inventory compliance status
IECSC	Contact supplier for inventory compliance status
KECL	Contact supplier for inventory compliance status
PICCS	Contact supplier for inventory compliance status
AICS	Contact supplier for inventory compliance status

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

Chemical Safety Report A Chemical Safety Assessment has been carried out for this substance

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H332 - Harmful if inhaled
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable liquids	On basis of test data

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 03-Aug-2021

Revision Number 1

VHG-SDSL-5000-100 - Sulfur Standard: S @ 5000 µg/g (0.500 wt%) in #2 Diesel Fuel

Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 03-Aug-2021

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise when using, handling and/ or storing the material. The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. LGC makes no warranties or representations as to the accuracy and completeness of the information contained herein, shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.

End of Safety Data Sheet